



Features and function of control are identical for both AutoMAB units!

- ▶ The control reliably monitors the drilling process, while the power consumption is displayed by means of an LED
- ▶ A safety cut-out protects the drilling motor from overload
- ▶ The high degree of uniformity in the drilling process protects the tool and machine and significantly reduces the risk of the core drill breaking
- ▶ Safety control cut-out: If the magnet loses its adhesion, the drilling and feed motors automatically cut out
- ▶ The automatic feed is activated by one of the three handles

AutoMAB 450	
Motor output	1,150 W
Voltage	230 V, 50 – 60 Hz
Stroke	160 mm
Magnet dimensions	168 x 84 x 48 mm
Weight	16 kg
Spindle taper	MT 2
Industrial arbor	MT 2, 19 mm (3/4")
Gear 1 range	250 rpm
Gear 2 range	450 rpm
Permanent internal lubrication	✓
LED power indicator	✓
Magnet indicator with safety cut-out	✓
Feed	Automatic feed/return
AutoMAB 450 230 V	
AutoMAB 450 110/125 V	

Included in delivery
1 Magnetic core drilling machine AutoMAB 450
1 Ejector pin ZAK 075 + 100
1 Ejector drift MT 2
1 Industrial arbor ZIA 219-KN, 19 mm Weldon (3/4")
1 Allen key size 5
1 Carry case
1 Safety lashing strap
1 Operating instructions

Core drill
Automatic feed
Max. Ø 45
Cutting depth
30-55 mm
Manual feed
Max. Ø 45
Cutting depth
30-55 mm

